

PROFICIENT
Protege[™]



Powered Floor Standing &
Passive Architectural Subwoofers

PROFICIENT
Protege
Powered Subwoofers

The new Proficient Protege subwoofers step up with more power, more deep bass and a whole lot more pop for music and movie lovers. They offer as much as +10dB more deep bass output than similar sized subwoofers on the market. That's more than you'd get by adding a second sub!

Each of the new Proficient Protege models features a powerful Class D amp, a rugged composite-cone woofer and a down-firing passive radiator that really brings out the ultra-deep bass notes. With line & LFE in, high-pass line out, volume, crossover and phase controls, these subs will hook up with almost any system.



FS12

Powered 12" Floor Standing Sub

Woofers: Two 12" Polypropylene-Coated Fiber Composite
One Front-Firing Active; One Down-Firing Passive

Amplifier Type: Class D Amp

Power Rating Continuous: 300 Watts RMS

Power Rating Peak: 600 Watts Peak

Frequency Response: 28Hz - 150Hz

Subwoofer Output: 106dB SPL

Inputs: Left & Right Line Level, LFE

Outputs: Line Level High-Pass

Phase Switch: 0 - 180°

Crossover: 50Hz - 150Hz; Bypass

Additional Features: Auto On, Anti-Clipping Circuitry

Cabinet: Black Wood Grain with Dampened Rubber Feet

Dimensions: H 16³/₈" x W 14¹/₂" x D 15¹/₂"

FS10

Powered 10" Floor Standing Sub

Woofers: Two 10" Polypropylene-Coated Fiber Composite
One Front-Firing Active; One Down-Firing Passive

Amplifier Type: Class D Amp

Power Rating Continuous: 250 Watts RMS

Power Rating Peak: 500 Watts Peak

Frequency Response: 30Hz - 150Hz

Subwoofer Output: 103dB SPL

Inputs: Left & Right Line Level, LFE

Outputs: Line Level High-Pass

Phase Switch: 0 - 180°

Crossover: 50Hz - 150Hz; Bypass

Additional Features: Auto On, Anti-Clipping Circuitry

Cabinet: Black Wood Grain with Dampened Rubber Feet

Dimensions: H 15¹/₈" x W 13¹/₄" x D 14"

FS8

Powered 8" Floor Standing Sub

Woofers: Two 8" Polypropylene-Coated Fiber Composite
One Front-Firing Active; One Down-Firing Passive

Amplifier Type: Class D Amp

Power Rating Continuous: 200 Watts RMS

Power Rating Peak: 400 Watts Peak

Frequency Response: 32Hz - 150Hz

Subwoofer Output: 100dB SPL

Inputs: Left & Right Line Level, LFE

Outputs: Line Level High-Pass

Phase Switch: 0 - 180°

Crossover: 50Hz - 150Hz; Bypass

Additional Features: Auto On, Anti-Clipping Circuitry

Cabinet: Black Wood Grain with Dampened Rubber Feet

Dimensions: H 13³/₈" x W 11³/₄" x D 12¹/₂"

PROFICIENT
Protege
Architectural Subwoofers

If you want massive bass but don't have the space, you want Proficient Protege architectural subs. They mount flush into walls and ceilings and with our thin-bezel design, you barely see them. But you'll definitely feel them. Our flagship is a dual 8-inch inwall that really pumps out the deepest notes distortion-free.

Proficient Protege architectural subwoofers are designed to work with our M3. It's a 180 watt high-current mono amp/crossover that delivers the power you need to rock any house. These subs are the best and easiest way to get high-impact bass with zero impact on interior design.



M3

Amp/Crossover Designed for ICS11, IWS105 & IWS85 Subwoofers

- 180 Watt High Current Mono Amp with Crossover
- Variable Low Pass Crossover: 35Hz - 150Hz
- LFE Input & Pass Through Output
- Remote Power-On Switching via Signal Sensing
- Includes Bolt-On Rack Ears
- Dimensions: H 4" x W 17 $\frac{1}{8}$ " x D 12 $\frac{3}{8}$ "

ICS11

Passive 10" Ceiling Sub

- Replaces ICS10 Ceiling Sub
- Woofer: 10" Long Excursion Graphite Cone
- Power Handling: 175 Watts RMS
- Frequency Response: 30Hz - 120Hz
- Includes Thin-Bezel Grille with Neo Magnets
- Dimensions: Diameter 13 $\frac{3}{8}$ " x Depth 6 $\frac{1}{2}$ "
- Ceiling Cut Out: Diameter 11 $\frac{7}{8}$ "

IWS105

Passive 10" Inwall Sub

- Replaces IWS100 Inwall Sub
- Woofer: 10" Long Excursion Treated Paper Cone w/Inverted Ferrite Magnet Structure
- Power Handling: 250 Watts RMS
- Frequency Response: 36Hz - 150Hz
- Includes Thin-Bezel Grille with Neo Magnets
- Dimensions: H 13 $\frac{3}{8}$ " x W 13 $\frac{3}{8}$ " x D 3 $\frac{3}{4}$ "
- Wall Cut Out: H 12 $\frac{1}{16}$ " x W 12 $\frac{1}{16}$ "

IWS85

Passive Dual 8" Inwall Sub

- Replaces IWS82 Inwall Sub
- Woofers: Two 8" Long Excursion Graphite Cones
- Power Handling: 200 Watts RMS
- Frequency Response: 30Hz - 120Hz
- Includes Thin-Bezel Grille with Neo Magnets
- Dimensions: H 20" x W 11 $\frac{1}{8}$ " x D 3 $\frac{1}{2}$ "
- Wall Cut Out: H 18 $\frac{1}{2}$ " x W 9 $\frac{3}{4}$ "

PROFICIENT®

1800 S McDowell Blvd • Petaluma, CA 94954 • 800.472.5555 • Fax 707.283.5901 • proficientaudio.com

©2015 Core Brands, LLC. All rights reserved. Proficient® is a registered trademark of Core Brands, LLC, a Nortek company.

SB0415